

The VT low temperature freezers creates the possibility to maintain temperatures as low as -45°C. Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.



DIMENSIONS		
Outer Dimensions HxWxD, mm	885x923x605	
Inner Dimensions HxWxD, mm	635x760x440	
Weight Gross/Net, kg	72 / 64	
Material inner cabinet	Painted Stee	
Material outer cabinet	Painted Steel	
Packaging weight, kg	8	
Packaging dimensions HxWxD, mm	900x973x72	
Insulation thickness, mm	80	
Insulation type	Polyurethane with Cyclopentane	
Mobility / Castors	Yes	
Refrigerant, Type	R290	
Number of compressors	1	
Internal Air Distribution	Static	
Number of Probes	1	
CONTROLLER		
Controller	XR30CX	
Controller language	No language - only 3 digit	
USB Connection	No	
Logging	No	
Temperature Graph	N	
High/Low Temp. Alarm	Yes	
Open Door Alarm	No	
Probe Failure Alarm	Yes	
Power Failure Alarm	No	
STORAGE		
Volume, Gross/net, L	198	
Baskets	1	
Basket material	Steel coated with plastic powder	
Inner lids	No	
FEATURES		
Lock	Yes	
LED Light	No	
Battery Backup for Controller, 24h	No	
Porthole	Yes - Ø 12 mm	
Dry Contact		
	No	
Door	No Solid	



BIOMEDICAL

The VT low temperature freezers creates the possibility to maintain temperatures as low as  $^{-}45^{\circ}\text{C}$ . Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

Frequency	Hz	50Hz
Max Ambient	°C	30°C
Max Humidity	% rh	55%
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	-25 to -45
Uniformity in performance - difference +/- from Avg set point	°C	6,4
Pull down time (from 25 to factory setpoint)	Minutes	90
Hold over time (from factory SP to -25, -40 and -60) Empty	Minutes	96
Refrigerant		R290
Number of probes	pcs	1
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	1
Safety thermostat	y/n	No
Energy 24 hours	kWh/24h	3,14
Energy year	kWh/year	1146,1

2